

## Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Texas - Warehousing solutions often focus on layout and space saving solutions in order to cut down on costly square footage and decrease travel time required to transport goods throughout the warehouse and loading dock areas. Narrow aisles need specific solutions to allow goods to be accessed and stored properly. More space can be given to storage as less space is needed for accessing the aisle. Configuring the warehouse is known as warehouse optimization. Warehouse Optimization There are several significant benefits of implementing very narrow aisle warehouse optimization. Since very narrow forklift trucks have been designed to take up significantly less space, warehouse aisle widths can be reduced to half the width needed by traditional forklifts. Numerous narrow aisle forklifts deliver better stacking heights to increase the storage capacity on a square foot basis. This means that costs are decreased because less warehouse space is necessary for the same amount of stock than if a standard aisle configuration were used. Square footage is costly in urban areas and any way to reduce warehousing costs can save a company money. Adding a very narrow aisle width system can increase storage up to eighty percent when planned properly. In addition, a very narrow aisle layout allows for more rack faces as well as better access to products. Since greater quantities of products are situated in a more accessible area, there is less travel time needed for gathering and storing items. It is common for warehouses to use a very narrow or narrow aisle layout. Narrow aisles are usually those that use less than 11 feet of aisle width. Very narrow aisles reduce the aisle width further to around six-and-a-half feet. Either of these widths drastically increases storage potential. Using a forklift for order picking and stocking can be difficult in these aisle widths, especially when turning. A variety of very narrow forklifts have been designed to easily maneuver in narrow aisles. Before choosing a forklift for a particular job, it is vital to know the dimensions of the aisle. Having the right aisle dimensions will save money and time instead of purchasing the wrong forklift that won't be able to conquer the applications. Taking note of any utilities, columns or posts is necessary before choosing a particular narrow aisle forklift design to maximize warehouse optimization and safety. Very Narrow Aisle Forklift Trucks Rechargeable batteries are typical for powering very narrow aisle forklift trucks and most models are electric. Very narrow aisle forklift trucks are popular as stand-up riders to help increase operator comfort and productivity. The most popular kinds of very narrow aisle forklift trucks include turret or swing-mast, end-control riders, order pickers and reach trucks. Reach Forklift Trucks The reach trucks were created as a type of rider stacker forklift but can be modified specifically for narrow aisle usage. The reach trucks developed their name from their forward-reaching actions to get a load. The moving mast and the moving carriage are two types of reach trucks. The moving carriage functions by lowering and raising the carriage and the operator. The moving mast raises and lowers the forks as the operator remains at ground level. Of the two kinds of reach trucks, the moving mast reach truck is the safer of the two varieties. These machines rely on a kind of jointed framework known as a pantograph system that enables the operator to place a load or reach the load without moving the machine. Order Pickers Order pickers have been created to pick items from difficult, high racking systems. These machines are used for picking up lighter stock that can be moved by hand. They lift the operator up to reach the goods by identifying and choosing certain items to create an order. End-Control Riders End-control riders are machines that pick loads up at floor level and move the items horizontally as opposed to lowering or lifting over numerous heights. Turret or Swing-Mast Forklift Swing-mast or turret very narrow aisle forklifts feature an articulating swivel mast that pivots. The mast swivels to enable pallets to be positioned on the right or left side of the forklift. Guided Very Narrow Aisle Trucks Very narrow aisle forklift trucks can be guided by rail or wire down the aisles. Since the forklift truck is guided, the chance of colliding with racks while traversing down the aisles is very low. Rail-guided applications use special rails set into the floor on either side of the aisle, funning the length of the location and curving around the edge. Wheel guides on the forklift slide into the floor rails to stop the machine from

traveling out of bounds. The wire-guidance system requires that the wires be installed into the floor, along the center of the aisle. The wire-guides function similarly to the rail systems except the forklift has a wire-guide system to prevent the machine from traveling where it is not supposed to. Work Site Considerations Certain essential considerations need to be dealt with before using a narrow aisle configuration. Because these very narrow aisle configurations include very tall racking systems, the condition of the floor and the construction of the racks must be done properly in order to avoid potentially disastrous outcomes. There are four areas which must be meticulously prepared before setting up a racking system and must be continuously monitored and maintained throughout the operation of the warehousing system: 1. The floor must be level; 2. Cracks must be repaired; 3. Load capacity of floor must be appropriate; and 4. The racks must be plumb.

**Level Floor** Due to the racking system height, any minor floor slope can gravely impact how plumb the racks are, particularly over time if loads are placed and removed repeatedly on the racks. The height of the racking system means that any minute floor slope can have a negative impact on how straight the racks are, especially over time when loads are continually removed and placed on the racks. Without this foundation of a level floor, the stability of the racks could be jeopardized. **Crack Repair** Cracks in the floor ideally should be fixed once they are noticed to ensure everyone's safety. Cracks may affect the floor's level and, when they are approximately 3/8 inches wide, will need to be properly filled with a material at least as hard as the surrounding floor. **Floor Load Capacity** The floor needs to meet specific minimum requirements prior to a narrow aisle configuration. At a minimum, the floor should consist of 3,000 psi concrete as well as contain evenly distributed rebar approximately 3 to 4 inches below the surface. Depending on the load requirements and configuration, additional reinforcements may be needed. **Plumb Racks** The racking system is essential to the whole process and needs to be installed properly. If installed improperly, there is a great chance of rack failure. All racks need to be plumb and this is one of the most vital aspects of correct installation. If necessary, rack shims should be used to ensure the racks are plumb within 1 inch at the 30 foot height of the racks. Dangerous racking failure can occur if the above steps are not taken. Racking failure can kill or injure employees, damage equipment and result in horrible damage. Due to these potential problems, the most significant part of creating a narrow aisle configuration for warehousing optimization is the initial measurements.